



**RUTOLAN FRANCE**  
DEPUIS 1983



## **FLUXAF® PRO ! DECAP A SEC NEW GENERATION PAINT STRIPPER WITHOUT DICHLOROMETHAN**

PACKAGING | 0.75L | 5L | 20L

### ***TYPE***

This universal liquid paint stripper is ready to use, and has a light smell. For dry stripping use without rinsing. Does not contain chlorinated solvents, acids, lyes, potash, or other dangerous solvents such as N.M.P, D-Limonene and is without preservatives. Neutral pH.

### ***PROPERTIES***

Fluxaf®Pro! Décap à Sec removes acrylic and latex paints, and different kind of varnishes (acrylic, cellulosic, synthetic resin based and asphalt, cellulosic dispersions, varnish with chlorinated rubber). If Fluxaf®Pro Décap à Sec is applied upon wood, it does not alter its color, but it is advisable to make a test on a discreet part for exotic woods.

We always advise to test the paint stripper on the most suitable small surface. Generously apply Fluxaf®Pro Décap à Sec on the surface to be stripped with a brush and leave to work during 5-15 minutes. Remove the stripped coats with a spatula, a scouring pad or a scraper. Repeat the operation if necessary. Slightly sand the surface before applying the finition coat. To be applied sheltered from the wind and sun in order to prevent the product to evaporate too quickly. Not suitable for interior use. Do not use with another stripping product. Leave to work during 5 to 15 minutes, depending on the coats thickness and oldness, and the ambient temperature.

### ***PRECAUTIONS***

Inflammable. Avoid contact with skin; repeated exposure can create skin dryness and cracks. Inhalation can create drowsiness and dizziness. Keep away from ignition source, do not smoke.

Do not inhale the vapors. Avoid contact with eyes and skin. In case of ingestion, immediately contact a doctor and show the safety data sheet. Apply in a well ventilated area. Keep in its original packaging away from heat, in a temperate area.

### ***RESIDUE TREATMENT***

The stripped materials (paint, glue, varnish, etc...) as well as the stripping residues can only be transported as chemical waste, according to the rules and directives of the local authorities. Contact the recycling centre. Empty and clean containers are recyclable.

Density 0.996g/cm<sup>3</sup>

Output :circa. 300-800 g/m<sup>2</sup>

Store away from frost in the tightly closed original container.

*The present notice is intended to inform our customers on our product's properties. The information contained therein is based on our current knowledge and is the result of tests with a constant concern of objectivity, depending on usage conditions, conforming to DTU or standards in force. No implicit or formal guarantee can be implied by this information*

## **SPECIALISTE DES PRODUITS PROFESSIONNELS DU SECOND-ŒUVRE**

*Naturellement vert*

ADRESSE POSTALE ET BUREAU  
RUTOLAN FRANCE SARL  
82 RUE DE FENOUILLET  
31200 TOULOUSE  
TEL. 33 (0)5 61 13 22 22  
FAX. 33 (0)5 61 14 31 31

SIEGE SOCIAL  
RUTOLAN FRANCE SARL  
8 BIS, RUE DE LA TRINITE  
31000 TOULOUSE  
RUTOLAN@RUTOLAN.COM  
WWW.RUTOLAN.COM

GAMME FLUXAF®  
DECAPANTS UNIVERSELS BIODEGRADABLES  
PROTECTION ET NETTOYAGE DES SURFACES  
ENTRETIEN & PROTECTION DU BOIS  
HUILES HOLLANDAISES  
MORTIER DE TOITURE FLEXIM®

BANQUE POPULAIRE N° 65321701405  
BIC CCBPFRPPTLS  
IBAN FR76 1780 7008 2165 3217 0140 531  
TVA NR. FR 55 329 033 294  
RCS TOULOUSE 329 033 294  
SIRET 329 033 294 00060

TOUS NOS DEVIS, CONSEILS, VENTES ET LIVRAISONS SONT SOUMIS A NOS CONDITIONS GENERALES DE VENTE AU DOS DE CETTE FEUILLE OU SUR [WWW.RUTOLAN.COM](http://WWW.RUTOLAN.COM)