

Fluxaf H2O STOP

Description:

Impregnation and water- repellent product, water based, for use on porous stone and concrete. Facades and objects (stone and concrete) are preserved against the (easily) infiltrating water and the buildup of pollution.

Instructions:

Remove dirt, dust and close any cracks (H2O Fluxaf STOP bridges cracks up to 1mm).

Stir before use.

Apply H2O STOP on (eventually wet) surface, with brush, roller or by spraying.

Apply till saturation. On very porous stone / concrete it might be necessary to apply a second coat after 10-20 minutes. Clean tools immediately after treatment with warm water (and soap).

Note: Fluxaf H2O STOP is only to be applied on surfaces being untreated or treated with a water-based impregnating product.

Notes:

- Very easy and economical to use: 1 liter is enough for 8-15m² (depending on application method and porosity of the surface).
- Immediate action: The treated surface is protected immediately after application against water and dirt.
- Invisible protection: Fluxaf H2O STOP causes to most types of stone very little or no change in color but on flat (or glazed or plain?) stones, it is recommended the product on a non-striking part to try first.
- Fluxaf H2O STOP prevents even the infiltration of water into cracks and crevices up to 1mm.
- As penetration of water is avoided, there is less risk of frost damage to the wall / object.

Applications not effected under our supervision exclude any responsibility or liability on the outcome and impact of that application. We always advise to do a test before using. Consult your advisor for specific types of application.