



RUTOLAN FRANCE
DEPUIS 1983

TECHNICAL DATA SHEET - RAW LINSEED OIL

USED FOR CENTURIES FOR THE PROTECTION OF THE WOOD AGAINST THE HUMIDITY, THE MUSHROOMS AND THE INSECTS, AND ALSO AGAINST THE DUST

THANKS TO ITS ANTISTATIC PROPERTIES, RAW LINSEED OIL COULD ALSO BE USED:

TO TREAT THE STEEL AGAINST RUST;

AND TO PROTECT TERRACOTTA FLOOR TILES



PACKAGING | 12*1 litre | 4*5 litres | 20 litres

TYPE

Raw linseed oil is produced by extraction of linseed or by pressing linseed.

CHARACTERISTICS

Raw linseed oil is a drying oil, which after processing, like boiling/cooking, blowing and/or polymerising dries even better. Paint based on linseed oil is very durable and elastic en has a high-grade shine.

Raw Linseed Oil could be used alone or mixed with other oils, resin and solvants such as indoor or outdoor wood protection.

APPLICATION

Because of the drying characteristics, excellently suitable for manufacturing paint and/or cement or for "greasing" of stain. The raw linseed oil is pre-eminently suitable as a wood preservative or steel protection against rust.

TRAITEMENT

Adding as needed to your extant recipes.

If it is used as a wood preservative to be applied lavishly with a brush.

If it is used as steel protection to be applied on one lay.

TECHNICAL DATA:

specific gravity ca.	0.931 , 25°C
appearance	liquid
colour Gardner ca.	12
refractive index	1,480 – 1.484 nD 20
acid number	max. 4 mg KOH/g
iodine number (Wijs)	min. 175
saponification number	188 - 195
insaponifiable percentage	< 1%

DRYING :

24 hours

The technical information and specifications contained in this data sheet are based on careful investigations and given to the best of our knowledge. Nevertheless circumstances under which the product is used in practice are subject to many variations. Rutolan France Sarl cannot be held responsible for possible deviations.

Naturellement vert

ADRESSE POSTALE ET BUREAU
RUTOLAN FRANCE SARL
82 RUE DE FENOUILLET
31200 TOULOUSE
TEL. 33 (0)5 61 13 22 22
FAX. 33 (0)5 61 14 31 31

SIÈGE SOCIAL
RUTOLAN FRANCE SARL
8 BIS, RUE DE LA TRINITE
31000 TOULOUSE
RUTOLAN@RUTOLAN.COM
WWW.RUTOLAN.COM

GAMME FLUXAF®
DECAPANTS UNIVERSELS BIODEGRADABLES
PROTECTION ET NETTOYAGE DES SURFACES
ENTRETIEN & PROTECTION DU BOIS
HUILES HOLLANDAISES
MORTIER DE TOITURE FLEXIM®

BANQUE POPULAIRE N° 65321701405
BIC CCBPFRPPTLS
IBAN FR76 1780 7008 2165 3217 0140 531
TVA NR. FR 55 329 033 294
RCS TOULOUSE 329 033 294
SIRET 329 033 294 00060

TOUS NOS DEVIS, CONSEILS, VENTES ET LIVRAISONS SONT SOUMIS A NOS CONDITIONS GENERALES DE VENTE AU DOS DE CETTE FEUILLE OU SUR WWW.RUTOLAN.COM